



STYROFOAM INSULATION AS PROVIDED WITH  
 THE THERMOMASS SYSTEM  
 REINFORCING PER STRUCTURAL ENGINEER  
 SLAB ON GRADE  
 EXPANSION JOINT WITH GROUT FILL  
 COIL ROD AND INBERT  
 INVERTED C-BAR FIBER COMPOSITE WYTHE TIE  
 COMPACTED FILL  
 REDUCED INSULATION  
 EARTH

SHIM AND GROUT AS REQUIRED  
 CONTINUOUS TRENCH FOOTING DESIGNED  
 AND REINFORCED AS REQUIRED BY  
 STRUCTURAL ENGINEER

COPYRIGHT 2006 COMPOSITE TECHNOLOGIES CORPORATION  
 THIS DRAWING IS THE EXCLUSIVE PROPERTY OF CTC.  
 ANY REPRODUCTION, COPY, OR OTHER UNAUTHORIZED USE OF  
 THIS DRAWING, INCLUDING BUT NOT LIMITED TO USE OF THIS  
 DRAWING IN THE INSTALLATION OF A NON-CTC INSULATION SYSTEM,  
 IS A VIOLATION OF U.S. COPYRIGHT LAWS AND OTHER RIGHTS OF CTC.  
 Composite Technologies Corporation  
 1000 Technology Drive., Boone, IA 50036  
 Wats: (800) 232-1748; Ph: (515) 433-6075; Fax: (515) 433-6088  
 Email: info@thermomass.com

PROJECT: <b>COMPOSITE WALL DETAIL FILE</b>	
DETAIL: <b>FOOTING</b>	
SCALE: <b>1 1/2" = 1'-0"</b>	
DRAWN BY: <b>TJB</b>	CHECKED BY: <b>DXN</b>
DATE: <b>02/14/06</b>	REVISION: <b>08/31/06</b>

CONFIGURATION: <b>3" / 2' / 3"</b>
PROJECT NO.:
DRWG. NO.: <b>CWT-F11</b>



**C-BAR TILT UP**